

FICHE TECHNIQUE PRODUIT

[Print](#)

▼ 530175 Tork Premium Multipurpose Cloth 530 Blanc Feuille à Feuille



Chiffon non-tissé très résistant: épais et absorbant
Résiste à l'eau, aux solvants et détergents
Sa surface à reliefs permet de faire disparaître les tâches de gras et les tâches rebelles
Protège les mains de la chaleur au moment de saisir des casseroles ou des plats chauds, et d'être coupé par des morceaux de métal
Contact alimentaire

▼ Information produit

Article	530175
int. Nom	Tork Premium Multipurpose Cloth 530 Blanc Feuille à Feuille
nat. Nom	TORK PREMIUM 530 BLANC HANDYBOX 120
Pays d'origine	Suameer
Code douanier	56039390
Plis	1
Grammage	80 [g/m ²]
Type de fibres	Non tissé
Impression	No
Longueur dépliée	64.2 [cm]
Longueur pliée	10.8 [cm]
Largeur dépliée	38.5 [cm]
Couleur	Blanche

▼ Spécifications du sous-conditionnement

Unités/sous-conditionnement	120
Poids brut	2.671 [kg]
Poids net	2.373 [kg]
Packaging	
EAN	7322540057584

▼ Spécifications du conditionnement

Packaging	Carton
Nombre de sous-conditionnement	1
Longueur	395 [mm]
Largeur	236 [mm]
Hauteur	238 [mm]
Volume	0.02219 [m ³]
Poids brut	2.671 [kg]
Poids net	2.373 [kg]
EAN	7322540057591

▼ Spécifications de la palette

Conditionnements/palette	70
Couches/palette	7
Volume	1.553 [m ³]
Hauteur	1816 [mm]
EAN	7322540124576

▼ Données environnementales



SCA HYGIENE PRODUCTS

Roissypôle – Le Dôme – Bâtiment 7, 95761 Roissy CDG Cedex, France. Tél. : 01 41 84 60 00, Fax : 01 41 84 62 52
www.tork.fr

FICHE TECHNIQUE PRODUIT

Chemical pulp Polypropene Polyester Chemicals

Chemical pulp

Chemical pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals and the major part of the lignin is removed. Chemical pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities.

There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free).

ECF is based on oxygene, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone.

ECF is used in this product.

Polypropene

Polypropene fibre is produced from polypropene resin. The resin is melted in an extruder and spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength.

Polyester

Polyester fibre is produced from terephtalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength.

Chemicals

Both functional and process chemicals are used. The functional chemical used is wetstrength agent. The wetstrength agent is a polyamide (from polyamidine/epichlorhydrinepolymer) with a very high affinity to the fibre.

Process chemical used is a surfactant.

This product is produced at Suameer mill, The Netherlands, and certified according to ISO 9001:2000, ISO 14001 and EMAS.

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destructed. The product itself is suitable for incineration. Contact local authorities before destruction.



SCA HYGIENE PRODUCTS

Roissypôle – Le Dôme – Bâtiment 7, 95761 Roissy CDG Cedex, France. Tél. : 01 41 84 60 00, Fax : 01 41 84 62 52
www.tork.fr